

Network Video Recorder

Natalus



4NA-NVR

8NA-NVR

16NA-NVR

Specifications

Model		Pro Series		
		4NA-NVR	8NA-NVR	16NA-NVR
Video	Camera input	4 PoE	8 PoE	16 PoE
	IP Camera	Spec	ONVIF 1812, RTSP, H.264/265, dual stream - upto 8MP	
		Num	4	8
	Output	1 HDMI (Main Display or Programmable HD Spot) 1 VGA (Main Display or Programmable HD Spot)		
Audio	Audio input	1 RCA		
	Output	1 RCA		
Sensor In		4(NC, NO selectable)	8(NC, NO selectable)	16(NC, NO selectable)
Alarm out		1 relay		
Operating System		Embedded Linux OS		
Display	Speed	Real Time		
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080, 2160x2440(4M UHD)		
	Split screen	1,4	1,4,6,8,9	1,4,6,8,9,13,16
Main IPC	CODEC	H.264		
	Resolution(Pixel) / fps	main : upto 8MP @ 30 dual : upto 960x540		
	Total Bitrate	200Mbps		
	Channel Bitrate	50 Mbps	25 Mbps	12.5 Mbps
Playback	Display	1,4	1,4,6,8,9	1,4,6,8,9,13,16
	Search mode	Calendar, Event , POS, Panorama, Thumbnail		
	Fast/Slow speed	0.25x~64x		
Backup device		External HDD, CD&DVD-RW, Network, Pen Drive		
Network Interface		Gigabit Ethernet		
The number of HDD		2 SATA + 1 eSATA(upto 12 bays, No capacity limit ; 10TB or more)		
Power Consumption		57.6W (48V)	96W (48V)	190W (SMPS)
Operating Temperature		0~40°C(32~104°F)		
Relative Humidity		Maximum 80% non-condensing		
Dimension		380(W)x340(D)x50(H) mm		



Security Warehouse India Pvt. Ltd.

C-63/4, Okhla Industrial Area, Phase –II, New Delhi -110020.

sales@natalus.co.in

Specifications subject to change without prior notice

WWW.SECURITYWAREHOUSE.CO.IN