

Explosion-Proof Housing

Natalus

ATEX IP68 Explosion Proof Camera Housing (SS304)

NA-1730-EX



Model	NA-1730-EX
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-40 °C to 60 °C (-49 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	Ex d IIC T6 Gb explosion-proof marking IP68, NEMA-6P enclosure rating
Input Power	24 V AC

Features

- IP68, NEMA-6P enclosure rating
- Operating temperature range from -40 °C to 60 °C (-49 °F to 140 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Included wiper and sunshield (optional)

Model	NA-1730-EX
	220 V AC, 50 Hz (optional)
Dimensions (W × H × L)	160 mm × 160 mm × 405 mm (6.3 in × 6.3 in × 15.9 in) (NA-1730-EX, NA-1730-EX-S) 160 mm × 200 mm × 405 mm (6.3 in × 7.9 in × 15.9 in) (NA-1730-EX-W, NA-1730-EX-S-W)
Internal Usable Size (Ø × L)	105 mm × 330 mm (4.1 in × 13.0 in)
Window Viewing Area (Ø)	73 mm (2.9 in)
Weight	8 kg (17.6 lb) (NA-1730-EX, NA-1730-EX-S) 9 kg (19.8 lb) (NA-1730-EX-W, NA-1730-EX-S-W)
Material	AISI 304 stainless steel (NA-1730-EX, NA-1730-EX-W) AISI 316L stainless steel (NA-1730-EX-S, NA-1730EX-S-W)
Heater Control	On at 1 °C ± 3 °C (34 °F ± 5 °F) (optional)
Related Products	-

Available Models

Model	Material	Accessory
NA-1730-EX	AISI 304 stainless steel	-
NA-1730-EX-S	AISI 316L stainless steel	-
NA-1730-EX-W	AISI 304 stainless steel	Wiper
NA-1730-EX-S-W	AISI 316L stainless steel	Wiper



Security Warehouse India Pvt. Ltd.

C-63/4, Okhla Industrial Area, Phase –II, New Delhi-110020.

sales@natalus.co.in

Specifications subject to change without prior notice

WWW.NATALUS.IN